


## On the Subject of Breakers

*Oh no, did I break something?*

- You must flip all of the breakers to the right.
- The black breakers may be flipped at any time.
- Only flip a colorful breaker when the black breakers are in the proper positions. Order breakers top to bottom.
- Use the first table below to determine the positions the black breakers must start in, based on the color of the colorful breaker to be flipped.
- From the starting position, flip the black breakers back and forth according to the criteria listed in the second table below before flipping the respective colorful breaker.



### Starting Position

Color of the Breaker	Highest Digit in the Serial Number				
	0-4	5-6	7	8	9
Red	RLLL	LLLR	RLRR	RRRL	RLRL
Blue	LLLL	RRLl	LRLR	LRRL	LLRL
Green	LRRR	LLRR	RLLR	LRLL	RRLR
Yellow	RRLR	LRRL	LLRL	RLRR	LRLR

### Further Adjustments

For each colorful breaker, from the starting position, flip each given black breaker every time a character given by the table appears in the serial number. Each black breaker may need to be flipped several times, but only final position matters.

Colorful Breaker	Black Breaker			
	1st	2nd	3rd	4th
1st	EG 4 9	IN 5 6	DT 2 3	CL 7 8
2nd	QU 2 8	PZ 3 7	HV 4 5	BW 6 9
3rd	JR 6 7	MX 2 9	KA 5 8	SF 3 4